

NEW PRODUCT
NOW AVAILABLE



VELLA

VENETIAN PLASTER SYSTEMS



VELLA LISCIO ULTRA SHEEN PLASTER

Vella Liscio Ultra Sheen Plaster is designed as a top coat over a Vella Venetian Plaster base coat, to achieve a high sheen polished plaster finish.

APPLICATION

STEP 1: Prepare by covering areas not to be plastered. Apply base coat to surface as evenly as possible. Cover textures or blemishes using a trowel, spatula or paint roller. Vella Liscio Ultra Sheen Plaster may be used over new or previously painted surfaces. Surfaces must be dry, clean, firm and free of dust, dirt, oil, wax, loose paint, wallpaper and plaster.

- ❖ When using a paint roller, use a trowel or spatula to smooth over any stipple left by the roller before the plaster dries. Plaster should dry overnight. Depending on weather conditions, fans may be used to speed up the drying process.

STEP 2: After Vella Base Coat dries, scrape any ridges or defects using a trowel or spatula, making base coat smooth to the touch. Remove any debris or dust away from corners and masked off areas before applying Vella Liscio Ultra Sheen Plaster. Using a random pattern apply a thin coat of Vella Liscio Ultra Sheen Plaster over the entire base coat using a trowel or spatula.

- ❖ Additional troweling of Vella Liscio Ultra Sheen Plaster after completing will produce an extremely high sheen to the finished surface.

STEP 3: After second coat dries (usually 4 hours, depending on weather conditions), apply a thin coat of Vella Premium Plaster Wax or sealer by sponge, rag or trowel to the entire surface. Final polishing of the surface should be done approximately 15 minutes after waxing using a dry rag or mechanical buffer.

MIXING

Add desired color (store will mix). If adding your own color, mix with drill and paddle.

COVERAGE

Vella Liscio Ultra Sheen Plaster covers approximately 450 square feet per gallon depending on application of product and surface preparation.

STORAGE

Store at room temperature with container tightly sealed.

CLEAN UP

Wash tools with water.

CAUTION

Avoid contact with eyes. May cause irritation. If contact occurs, flush immediately with water and contact physician immediately. This product is not recommended for embedding tape. For interior use only.

If sanding is necessary, use a dust-particulate respirator approved by NOSHA-MSHA.



VELLA PART#	DESCRIPTION	SIZE	WEIGHT	UPC CODE
30002	VELLA LISCIO ULTRA SHEEN PLASTER	1 GAL.	11 LBS.	0 0051 630060 1

SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • WWW.VELLAPLASTER.COM

SUBMITTAL APPROVALS

JOB NAME:

CONTRACTOR:

DATE:

SALES AND ORDER INFORMATION

145 WEST MEATS AVENUE • ORANGE, CALIFORNIA 92865

OFFICE: 714.279.0240 • FAX: 714.279.1043 • WWW.VELLAPLASTER.COM