



# Mission One-Coat Sealer

Interior/Exterior 100% Acrylic Finish

Architectural Coating - Premium Plus

## Description

Victory Stone Sealer is a premium plus 100% acrylic enamel for interior and exterior surfaces. This top-of-the-line enamel provides block resistance with excellent scrub ability and durability. This sealer exhibits exceptional stain and dirt resistance with excellent hide and adhesion. This can be used in areas where oil based products were previously required. Excellent choice for use on commercial, residential, institutional or custom painting projects, and the perfect sealer for Mission One-Coat and other plaster applications.

## Recommended Uses

Properly primed drywall, concrete, masonry, wood and metal.

## Colors

White, stock.

## Packaging

Quart, one and five gallon containers

## Finish

Eggshell, sheen @ 60° = 14.0 - 18.0%

## Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

## Primer

Drywall (New):	1100Hi-Build Sealer
Drywall (Existing):	4000Uniprime
Concrete/Masonry:	4600Uniprime II
Wood (Exterior):	4200Terminator II
Wood (Interior):	188Acrylic Primer
	6600AquaLac Undercoat
Ferrous Metal:	9600 Protec Metal Prime White
	9610Protec Metal Prime
	Red Oxide
Non-Ferrous Metal	4800Metal Pro Primer White
	4810Metal Pro Primer
	Red Oxide

## Application

Sponge is used for best results over smooth, color-integrated Mission One-Coat plaster. Apply in small circles to ensure full coverage. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

## Drying Time

Touch:	1 hour
Recoat:	4 - 6 hours

## Coverage

300 - 400 square feet per gallon, depending on surface and application.

## Mil Thickness

Wet = 4.3	Dry = 1.5
-----------	-----------

## Thinning

Use at package consistency. If thinning is required, use water sparingly.

## Composition

TOTAL PIGMENT	29.0%
Titanium Dioxide	18.6%
Extenders	10.4%
TOTAL VEHICLE	71.0%
Acrylic Resin	21.3%
Additives	8.5%
Water	41.2%

## Weights & Measurements +/-3.0%

Solids by Volume:	36.0%
Solids by Weight:	50.3%
VOC:	50 g/l
Weight Per Gal:	10.8 lbs.
Viscosity:	96 - 100 KU

## Certification

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with GS-11 / EQ 4.2.

Green Wise - tested and certified

MPI - #15, #52 and #139

CHPS - passess Section 01350 testing

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.