

NEW



VICTORY
STONE

INTERIOR PLASTER WALL FINISHES

Natural, Polished & Mission One-Coat

- *Authentic Marmorino Finishes*
- *Highly Durable Crushed Marble Based Plaster*
- *Made in the USA*
- *Applied Directly Over Level 3 Drywall Finish*
- *Applied Over Existing Painted Texture Surfaces Without Primer*
- *Can Match Any Marmorino Plaster In The Marketplace; From Smooth/Contemporary To Rustic Old-World*
- *May Be Applied Wet on Wet for Multi-Color Marble Finishes*
- *No Bonding Agent Required*
- *Lowest cost and easiest application on the market*
- *Interior Application Only*

Victory Stone 'Natural'

For a natural stone finish, this is the most subtle on the product line.

Victory Stone 'Polished'

A higher sheen version of the 'Natural'. Great for modern and contemporary finishes, this product provides a smooth and polished surface, like marble.

Victory Stone 'Mission One-Coat'

This is the coarsest product on the line, providing amazing 'exposed aggregate' finishes IN ONE COAT! Use of 'Mission One-Coat 100% Acrylic Sealer' keeps the product feeling natural and open, while providing great protection. (May be applied in 2 coats for dramatic old-world texture.)

Preparation

Prepare by covering to protect adjacent areas and substrates. Product may be used over new or previously painted surfaces. Surfaces must be dry, clean, free from dust, dirt, oil, wax, loose paint, wallpaper glue, etc. (Pre-priming is recommended over wallpaper removal surfaces and allowed to dry, to prevent residue from re-emulsifying). Begin application by making sure product is properly mixed using a drill motor and paddle to achieve an ideal viscosity. Thinning of product is not required.

Application

Basecoat: Apply using a Hawk & Trowel or Pan & Knife method and putty coat product over the entire surface. Once material begins to set up, use a trowel or broad knife to completely smooth out lap-lines if less movement and a more uniform color is desired. Otherwise, you may scrape down highpoints when dry for added character. Keep knife flat or use a trowel to avoid chatter marks.

Topcoat: Much less material is used on this coat, product is pulled very tight with flat knife or trowel. Cover basecoat completely for smooth finishes, leave pockets of basecoat showing when texture is desired. May be trowelled as the product sets up to add mottling and close the pores for a smooth finish. Leave open for all exposed aggregate finishes.

All products must be sealed, sponge applied M1C Sealer or Vella Wax preferred.

Coverage

Victory Stone Products cover +80 ft² per gallon with 2 coats. Mission One-Coat will yield less if applied. Results may vary depending on application of product and surface preparation.

Storage

Store at room temperature with container tightly sealed.

Clean Up

Wash tools with water.

Caution

Avoid contact with eyes. May cause irritation. If contact occurs, flush immediately with water and contact physician immediately. This product is not recommended for embedding tape. For interior use only. If sanding is necessary, use a dust-particulate respirator approved by NOSHA-MSHA.



70002, 70003, 70004	Victory Stone Natural	3.5 Gal, 1 Gal, 1 Qt	42lbs, 12 lbs, 3 lbs
70006, 70007, 70008	Victory Stone Polished	3.5 Gal, 1 Gal, 1 Qt	42lbs, 12 lbs, 3 lbs
70010, 70011, 70012	Mission One-Coat	3.5 Gal, 1 Gal, 1 Qt	42lbs, 12 lbs, 3 lbs

SALES AND ORDER INFORMATION

145 West Meats Avenue • Orange, California 92865

Office: 714-279-0648 • Fax: 714-279-1043 • www.victorystonewall.com

SUBMITTAL APPROVALS

JOB NAME: _____

CONTRACTOR: _____ DATE: _____

SALES AND ORDER INFORMATION
145 West Meats Avenue • Orange, California 92865
Office: 714-279-0648 • Fax: 714-279-1043 • www.victorystonewall.com